

## FLAMMABILITY TEST CERTIFICATE – 77751

**COMPANY DETAILS:** BANCROFT SOFT FURNISHINGS  
6 RUSSELL COURT, WOOL GATE, COTTONGLEY BUSINESS PARK,  
BINGLEY, BD16 1PE

**CONTACT NAME(S):** REBECCA PETERSON  
**TEL:** 01274 518888  
**EMAIL:** [rebecca.peterson@bancroft-linings.com](mailto:rebecca.peterson@bancroft-linings.com)

**DATE RECEIVED:** 27/09/2019  
**DATE TESTED:** 02/10/2019  
**DATE ISSUED:** 02/10/2019  
**PO NUMBER:** BSF 237

**SAMPLE DESCRIPTION:** 7041 DIAMOND FR BLACKOUT  
**COLOUR:** NOT STATED  
**QUALITY/BATCH REF:** NOT STATED  
**COMPOSITION:** 100% POLYESTER  
**MODEL NO:** NOT STATED  
**SAMPLE END USE:** DRAPERY  
**MANUFACTURER:** NOT STATED  
**SUPPLIER/BUYER:** NOT STATED

### REQUIREMENT/CLASSIFICATION:

BS EN 13773: 2003 – Textiles and textile products – Burning behaviour – Curtains and drapes classification scheme

### TEST METHODS:

BS EN 1101: 1996 – Burning behaviour of curtains & drapes. Detailed procedure to determine the ignitibility of vertically orientated specimens (Small flame)

BS EN 13772: 2011 – Textiles and textile products – Burning behaviour – Curtains & Drapes – Measurement of flame spread of vertically oriented specimens with large ignition source

### PRE-TREATMENT:

The sample had not been subjected to any cleansing procedure prior to testing.

### CONDITIONING:

The sample was conditioned for at least 24 hrs in a specified atmosphere at  $20 \pm 2^{\circ}\text{C}$  and  $65 \pm 5\%$  r h.

Authorised By:



Zeb Alam  
Operations Director

Mark Jones  
General Manager

Karen Brooks  
Managing Director

Please note: The uncertainty of measurement is taken into account when stating conformance to the specification. The measured value(s) marked\* are compared with the 'acceptance interval' which is determined by reducing the specification limits by the expanded test uncertainty  $U_k=2$  (approximately 95% confidence interval). Results outside these limits are declared as 'fail'. All test results issued on this certificate refer only to the item under test as supplied by the customer. This test certificate shall not be duplicated. Textile Innovation House, 1 Lyons Road, Trafford Park, Manchester, M17 1RN T: 0161 50 50 650 E: [technical@ifs-labs.com](mailto:technical@ifs-labs.com)

## FLAMMABILITY TEST CERTIFICATE – 77751

TEST RESULTS: BS EN 1101: 1996

TEST NUMBER	FLAME APPLICATION TIME	RESULT	TEST NUMBER	FLAME APPLICATION TIME	RESULT
1	1s	No-Ignition	7	15s	No-Ignition
2	2s	No-Ignition	8	20s	No-Ignition
3	3s	No-Ignition	9	20s	No-Ignition
4	4s	No-Ignition	10	20s	No-Ignition
5	5s	No-Ignition	11	20s	No-Ignition
6	10s	No-Ignition	12	20s	No-Ignition

TEST RESULTS: BS EN 13772: 2011

Test Criteria	1	2	3	4	5	6
Specimen Direction:	↑	↓	↑	←	→	←
Application Time:	10	10	10	10	10	10
Flaming Duration:	0.0	0.0	0.0	0.0	0.0	0.0
1 <sup>st</sup> Marker thread Severed?	NO	NO	NO	NO	NO	NO
3 <sup>rd</sup> Marker thread Severed?	NO	NO	NO	NO	NO	NO
Flaming Debris	NO	NO	NO	NO	NO	NO
Damage Length: (mm)	169	182	171	186	160	177
<b>Result</b>	<b>CLASS 1</b>	<b>CLASS 1</b>	<b>CLASS 1</b>	<b>CLASS 1</b>	<b>CLASS 1</b>	<b>CLASS 1</b>

### CLASSIFICATION

CLASS	IGNITIBILITY	FLAME SPREAD
1	Non Ignition according to EN 1101	1 <sup>st</sup> Marker thread not severed, no flaming debris, according to EN 13772
2	Non Ignition according to EN 1101	3 <sup>rd</sup> Marker thread not severed, no flaming debris, according to EN 13772
3	Non Ignition according to EN 1101	3 <sup>rd</sup> Marker thread severed, and/or flaming debris, according to EN 13772
4	Ignition according to EN 1101	3 <sup>rd</sup> Marker threads not severed, and no flaming debris, according to EN 1102
5	Ignition according to EN 1101	3 <sup>rd</sup> Marker threads severed, and/or flaming debris, according to EN 1102

### CONCLUSION:

The sample supplied has achieved a **CLASS 1** in accordance with BS EN 13773: 2003

Please note: The uncertainty of measurement is taken into account when stating conformance to the specification. The measured value(s) marked\* are compared with the 'acceptance interval' which is determined by reducing the specification limits by the expanded test uncertainty  $U_k=2$  (approximately 95% confidence interval). Results outside these limits are declared as 'fail'. All test results issued on this certificate refer only to the item under test as supplied by the customer. This test certificate shall not be duplicated. Textile Innovation House, 1 Lyons Road, Trafford Park, Manchester, M17 1RN T: 0161 50 50 650 E: technical@ifs-labs.com

END OF REPORT