

## FLAMMABILITY TEST CERTIFICATE – 73553 AMENDED

**COMPANY DETAILS:** BANCROFT SOFT FURNISHINGS  
6 RUSSELL COURT, WOOL GATE, BINGLEY, BD16 1PE

**CONTACT NAME(S):** REBECCA PETERSON  
**TEL:** 01274 518888  
**EMAIL:** [rebecca.peterson@bancroft-linings.com](mailto:rebecca.peterson@bancroft-linings.com)

**DATE RECEIVED:** 08/03/2019  
**DATE TESTED:** 13/03/2019  
**DATE ISSUED:** 15/03/2019  
**PO NUMBER:** BSF 200

**SAMPLE DESCRIPTION:** 7081 MAZZA UPHOLSTERY  
**COLOUR:** CORAL  
**QUALITY/BATCH REF:** P11674  
**COMPOSITION:** 100% POLYESTER  
**SAMPLE END USE:** NOT STATED  
**MANUFACTURER:** NOT STATED  
**SUPPLIER/BUYER:** NOT STATED

### SPECIFICATION/REQUIREMENT:

BS 7176:2007+A1:2011 – Specification for the resistance to ignition of upholstered furniture for non-domestic seating by testing composites. (Medium Hazard)

### TEST METHOD(S):

BS EN 1021-1:2006 – Furniture – Assessment of the ignitibility of mattresses and upholstered bed bases. Part 1: Ignition source smouldering cigarette.

BS EN 1021-2:2006 – Furniture – Assessment of the ignitibility of mattresses and upholstered bed bases. Part 2: Ignition source match flame equivalent.

BS 5852:2006 – Methods of test for the assessment of the ignitibility of upholstered seating by smouldering and flaming ignition sources.

### PRE-TREATMENT:

Water Soak procedure in accordance with Annex D of BS EN 1021-1:2006 & Annex E of BS 5852:2006

### CONDITIONING:

The sample was conditioned for 72 hrs in ambient conditions for at least 24 hrs in a specified atmosphere at  $23 \pm 2^{\circ}\text{C}$  and  $50 \pm 5\%$  r h.

Authorised By:

Zeb Alam  
Operations Director



Mark Jones  
Quality Manager

Karen Brooks  
Managing Director

Please note: this test results issued on this certificate refer only to the item tested and therefore doesn't relate to the lot or batch of the product / sample. This test certificate shall not be duplicated. Textile Innovation House, 1 Lyons Road, Trafford Park, Manchester, M17 1RN. T: 0161 50 50 650 E: [technical@ifs-labs.com](mailto:technical@ifs-labs.com)

## FLAMMABILITY TEST CERTIFICATE – 73553 AMENDED

### TEST RESULTS:

“The Following test results relate only to the ignitibility of the combination of the materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.”

TEST CRITERIA – 1021-1 (CIGARETTE TEST)	INITIAL TEST	REPEAT TEST
FILLING MATERIAL USED:	CMHR 35	CMHR 35
Cigarette ceased smouldering within (Min(s))	<60.0	<60.0
<b>PROGRESSIVE SMOULDERING CRITERIA (3.1)</b>		
Unsafe escalating combustion (3.1a)	NO	NO
Smoulders to extremities (3.1b)	NO	NO
Smoulders through thickness (3.1c)	NO	NO
Smoulders for more than 1 hr (3.1d)	NO	NO
Presence of active smouldering on final examination? (3.1e)	NO	NO
Evidence of melting, charring, dripping?	Melting: <input checked="" type="checkbox"/>	Charring: <input checked="" type="checkbox"/> Dripping: <input type="checkbox"/>
<b>FLAMING CRITERIA (3.2)</b>		
Cover Split?	NO	NO
Occurrence of flames?	NO	NO
<b>TEST RESULT</b>	<b>PASS</b>	<b>PASS</b>

TEST CRITERIA – 1021-2 (MATCH TEST)	1 <sup>st</sup> Test	2 <sup>nd</sup> Test	3 <sup>rd</sup> Test
FILLING MATERIAL USED:	CMHR 35	CMHR 35	CMHR 35
Cigarette ceased smouldering within (Min(s))	0.0	0.0	0.0
<b>PROGRESSIVE SMOULDERING CRITERIA (3.1)</b>			
Unsafe escalating combustion (3.1a)	NO	NO	NO
Smoulders to extremities (3.1b)	NO	NO	NO
Smoulders through thickness (3.1c)	NO	NO	NO
Smoulders for more than 1 hr (3.1d)	NO	NO	NO
Evidence of melting, charring, dripping?	Melting: <input checked="" type="checkbox"/>	Charring: <input checked="" type="checkbox"/> Dripping: <input type="checkbox"/>	
<b>FLAMING CRITERIA (3.2)</b>			
Unsafe escalating combustion (3.2a)	NO	NO	NO
Test assembly consumed (3.2b)	NO	NO	NO
Flaming to extremities and thickness (3.2c) (3.2d)	NO	NO	NO
Flaming continued for more than 120 seconds	NO	NO	NO
Cover split?	NO	NO	NO
<b>TEST RESULT</b>	<b>PASS</b>	<b>PASS</b>	<b>PASS</b>

## FLAMMABILITY TEST CERTIFICATE – 73553 AMEDNED

TEST RESULTS continued:

TEST CRITERIA – BS 5852:2006 Source 5	INITIAL TEST	REPEAT TEST
Flaming Ceased:	03.50	04.29
<b>PROGRESSIVE SMOULDERING CRITERIA (4.1)</b>		
<b>FILLING MATERIAL USED:</b>	CMHR 35	CMHR 35
b) Detectable amounts of smoke, heat or glowing 60 mins after crib ignition?	NO	NO
c) Displays unsafe escalating combustion, requires to be forcibly extinguished?	NO	NO
d) Smouldering consumed the test specimen within the duration of the test?	NO	NO
e) Smoulder to the extremities i.e. upper or lower margins, either side or to its full thickness?	NO	NO
f) On final inspection, any evidence of charring more than 100 mm in any direction (apart from upwards) from the original nearest position?	NO	NO
<b>FLAMING CRITERIA (4.2)</b>		
b) Flaming continued for more than 10 minutes after the ignition of the crib?	NO	NO
c) Displays unsafe escalating combustion, requires to be forcibly extinguished?	NO	NO
d) Flaming and/or smouldering consumed the test specimen within the duration of the test?	NO	NO
e) Flame front reaches the lower margin, either side or passes through the full thickness?	NO	NO
<b>TEST RESULTS</b>	<b>PASS</b>	<b>PASS</b>

### CONCLUSION:

The sample supplied **meets** the test criteria of BS 7176:2007 + A1:2011 (Medium Hazard)

END OF REPORT